



Fisher Scientific accumet® AB200 pH/Conductivity/Temp Meter

An Accurate, Affordable, Multi-Parameter Instrument

- » New model measures pH & Conductivity/TDS/Resistivity/Salinity
- » Choose to display one parameter or pH and another parameter together
- » Graphic LCD with adjustable backlight
- » Date and time to meet GLP
- » Password protection
- » Optional calibration reminder & high/low alarm
- » 500 point memory – log manually or at intervals
- » Easily view calibration data

For best results, connect optional 13-620-BSP stirrer (see page 13) for efficient mixing and fast, accurate measurements!



Kit includes 13-620-100 cell.
For other conductivity cells, see page 14.

The AB200 is a multi-parameter instrument capable of measuring pH, temperature, conductivity, total dissolved solids, resistivity, and salinity. Temperature is measured in two channels; a high accuracy thermistor built-in to the conductivity probe, or separately along with the pH reading.

A generous graphic backlit display makes the AB200 meter easy to read, while plain language prompts and error messages guide the user through measurements and calibrations. Change the display view with a press of a button.

Specifications and Ordering Information

pH Mode	
Range	-2.000 to 20.000 pH
Resolution	0.1 / 0.01 / 0.001 pH
Accuracy	±0.002 pH + 1 LSD
Buffer Sets	USA: 2.000, 4.010, 6.997, 10.013, 12.000 NIST: 1.678, 4.010, 6.865, 9.184, 12.460 DIN: 1.090, 3.060, 4.650, 6.790, 9.230, 12.750 FSCI: 1.000, 3.000, 6.000, 8.000, 10.000, 13.000 CUSTOM: Any 2-5 values, ≥1.0 pH unit apart
Slope Display	Yes, up to 5 different slopes with offset
Temp Compensation	Automatic or manual (0 to 100 °C / 32 to 212 °F)
mV Mode	
Range	±2000.0 mV / Rel. mV
Resolution	0.1 mV
Accuracy	±0.2 mV or ±0.05 % whichever is greater
Offset Adjustment	Up to ±150 mV
Temperature Mode	
Resolution	0.1 °C / 0.1 °F
Accuracy	±0.3 °C / ±0.5 °F
Calibration	Offset in 0.1 ° increments; offset range: ±5 °C / 9 °F
Conductivity Mode	
Range	0.00 µS to 500.0 mS
Resolution	0.01 / 0.1 µS ; 0.001 / 0.01 / 0.1 mS
Accuracy	±1 % full scale
Coefficient (Per °C)	Linear & pure ; adjustable 0.000 to 10.000 %
Normalization	15.0 to 30.0 °C
TDS Mode	
Range	0.00 ppm to 500 ppt (@ TDS factor 1.00)
Resolution	0.01 / 0.1 ppm ; 0.001 / 0.01 / 0.1 ppt
Accuracy	±1 % full scale
TDS Factor	0.400 to 1.000
Salinity Mode	
Range	0 to 80.0 ppt
Resolution	0.01 / 0.1 ppm ; 0.001 / 0.01 / 0.1 ppt
Accuracy	±1 % full scale
Resistivity Mode	
Range	2.000 Ω to 20.0 MΩ
Resolution	0.01 / 0.1 Ω ; 0.001 / 0.1 kΩ ; 0.01 MΩ
Accuracy	±1 % full scale
Output	RS-232 (phono plug), mini-B USB, stirrer
Language Selection	English, Deutsch, 中文, Français, Italiano, & Español
Memory	500 data sets, viewable
Datalogging	Manual, timed (selectable every 3 to 3600 seconds) Printer or CSV format
Cal Due Alarm	Yes, user selectable from 8 hrs, 16 hrs, & 1-31 days
High / Low Alarms	Yes, user selectable, visual & audible

AB200 Meter Kit: Includes meter, TRIS compatible pH/ATC electrode (13-620-631), Conductivity/Temp probe (13-620-100), electrode arm, RS-232 & USB cables, 100/240 V power supply, and manual.

AB200 Meter Only: Includes meter, electrode arm, RS-232 & USB cables, 100/240 V power supply, and manual.

Description	Catalog No.
AB200 Kit	13-636-AB200
AB200 Meter Only	13-636-AB200A
Fisher Scientific accumet® Benchtop Stirring Probe	13-620-BSP