

GC Septa

Quality materials for all applications



BTO Septa

- Low bleed septa - ideal for MS applications
- Excellent mechanical properties
- Maximum temperature 400°C

TR-Green Septa

- Long injection lifetime
- Low injection port adhesion
- Maximum temperature 400°C

Marathon Septa

- Pre-pierced for reliable performance
- Up to 400 injections per septa
- Maximum temperature 400°C

TR-Blue Septa

- General purpose septa
- Easy to penetrate
- Maximum temperature 200-250°C

Septa

Material	ID (mm)	Cat. No.	Quantity
BTO	9	31303240	50 Pack
BTO	11	31303233	50 Pack
BTO	11.5	31303230	50 Pack
BTO	12.7	31303228	50 Pack
BTO	17	31303211	50 Pack
TR-Green	9	313G3240	50 Pack
TR-Green	11	313G3230	50 Pack
TR-Green	12	313G3228	50 Pack
TR-Green	17	313G3211	50 Pack
Marathon	9	313P3240	50 Pack
Marathon	11	313P3233	50 Pack
Marathon	11.5	313P3230	50 Pack
Marathon	17	313P3211	50 Pack
TR-Blue	9	313B3240	50 Pack
TR-Blue	11	313B3233	50 Pack
TR-Blue	11.5	313B3230	50 Pack
TR-Blue	17	313B3211	50 Pack